

BLANCO MIKADO

Cold buffet with active contact cooling	160
Cold buffet with active convection cooling.	162
Hot buffet	163
Plain buffet	165
Servery counter	167
Accessories for MIKADO	168
LAS VEGAS, MANHATTAN	170





BLANCO MIKADO
MANHATTAN
LAS VEGAS

MIKADO – Cooled servery counter with active contact cooling 3 x GN 1/1

- Mobile module with one-piece cooling trough equipped with outside cooling coils and CFC-free foamed insulation
- 1/2" drain with ball valve for cleaning or draining melted ice water
- Refrigerant: R 134 a, CFC-free
- Paneling: 18/10 stainless steel
- Top surface of 18/10 stainless steel, height of edge: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Operating modules on long side, installed ready to plug in incl. helix cord that can be drawn out to a length of approx. 2 m
- On/Off switch, On/Off switch for light, electronic temperature control with digital temperature display
- Cooling range: from +8°C to +15°C, set to +7°C at the factory
- Sneeze guard on both sides of 6 mm thick, curved tempered safety glass (ESG), supported by two stainless-steel round-tube stands each
- Stainless-steel lighting shelf with two fluorescent tubes (2x18 W)
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO – SKS-3 and SKM-3

Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Capacity	Order No.
	MIKADO-SKS-3	Cooled servery counter with active contact cooling, thin base	1217 x 675 x 1475 mm	3 x GN 1/1 max. depth: 150 mm	572 124
	MIKADO-SKM-3	Cooled servery counter with active contact cooling, solid base	1217 x 675 x 1475 mm	3 x GN 1/1 max. depth: 150 mm	572 127

Equipment



Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1155 x 1250 mm
	2.2 yellow and white	
	2.3 blue and white	
	2.4 green and white	
Glass shelf	3.1 Glass shelf, tempered safety glass (ESG)	1085 x 270 x 8 mm
Railing	4.1 Railing for glass shelf, stainless-steel round tube	
Lighting shelf	5.1 Stainless-steel with 2 fluorescent tubes of 18 W each	1115 x 80 x 40 mm
	5.2 Stainless-steel with 3 low-voltage halogen lamps of 20 W each	
Tray slide	6.1 Stainless-steel round tube, operator side/customer side, fold-down	1228 x 235 mm
Tray slide	7.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1228 x 280 x 30 mm
Plate slide	8.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1228 x 153 x 30 mm
Side shelf	9.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	10.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Castor model	11.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	11.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard for line modules	12.1 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm	
	12.2 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through	
Module connection	12.3 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	

MIKADO – Cooled servery counter with active contact cooling 4 x GN 1/1

- Mobile module with one-piece cooling trough equipped with outside cooling coils and CFC-free foamed insulation
- 1/2" drain with ball valve for cleaning or draining melted ice water
- Refrigerant: R 134 a, CFC-free
- Paneling: 18/10 stainless steel
- Top surface of 18/10 stainless steel, height of edge: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Operating modules on long side, installed ready to plug in incl. helix cord that can be drawn out to a length of approx. 2 m
- On/Off switch, On/Off switch for light, electronic temperature control with digital temperature display
- Cooling range: from +46.40°F to +15°C, set to +7°C at the factory
- Sneeze guard on both sides of 6 mm thick, curved tempered safety glass (ESG), supported by two stainless-steel round-tube stands each
- Stainless-steel lighting shelf with two fluorescent tubes (2x18 W)
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO – SKS-4 and SKM-4

Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Capacity	Order No.
	MIKADO-SKS-4	Cooled servery counter with active contact cooling, thin base	1542 x 675 x 1475 mm	4 x GN 1/1 max. depth: 150 mm	569 939
	MIKADO-SKM-4	Cooled servery counter with active contact cooling, solid base	1542 x 675 x 1475 mm	4 x GN 1/1 max. depth: 150 mm	572 126

Equipment


Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1480 x 1250 mm
	2.2 yellow and white	
	2.3 blue and white	
	2.4 green and white	
Glass shelf	3.1 Glass shelf, tempered safety glass (ESG)	1410 x 270 x 8 mm
Railing	4.1 Railing for glass shelf, stainless-steel round tube	
Lighting shelf	5.1 Stainless-steel with 2 fluorescent tubes of 18 W each	1440 x 80 x 40 mm
	5.2 Stainless-steel with 4 low-voltage halogen lamps of 20 W each	
Tray slide	6.1 Stainless-steel round tube, operator side/customer side, fold-down	1553 x 235 mm
Tray slide	7.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 280 x 30 mm
Plate slide	8.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 153 x 30 mm
Side shelf	9.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	10.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Castor model	11.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	11.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard for line modules	12.1 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm	
	12.2 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through	
Module connection	12.3 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	

MIKADO – Cooled servery counter with active convection cooling 4 x GN 1/1

- Mobile module with edged convection-cooling trough, CFC-free insulation
- Removable cooling trough, large-area finned evaporator located below, which can be folded up for easier cleaning
- Refrigerant: R 134 a, CFC-free
- Paneling: 18/10 stainless steel
- Top surface of 18/10 stainless steel, height of edge: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Operating modules on long side, installed ready to plug in incl. helix cord that can be drawn out to a length of approx. 2 m, Schuko plug
- On/Off switch, On/Off switch for light, electronic temperature control with digital temperature display and automatic defroster
- Cooling range: from +2°C to +15°C, set to +7°C at the factory
- Suitable for cooling food with a max. temperature of +7°C required for hygienic reasons.
- Sneeze guard on both sides of 6 mm thick, curved tempered safety glass (ESG), supported by two stainless-steel round-tube stands each
- Stainless-steel lighting shelf with two fluorescent tubes (2x18 W)
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO-UKM-4

Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Capacity	Order No.
	MIKADO-UKM-4	Cooled servery counter with active convection cooling, solid base	1542 x 675 x 1475 mm	4 x GN 1/1 max. depth: 200 mm or max. 8 salad bowls (dia. 260 mm)	569 940

Equipment



Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1480 x 1250 mm
	2.2 yellow and white	
	2.3 blue and white	
	2.4 green and white	
Glass shelf	3.1 Glass shelf, tempered safety glass (ESG)	1410 x 270 x 8 mm
Railing	4.1 Railing for glass shelf, stainless-steel round tube	
Lighting shelf	5.1 Stainless-steel with 2 fluorescent tubes of 18 W each	1440 x 80 x 40 mm
	5.2 Stainless-steel with 4 low-voltage halogen lamps of 20 W each	
Tray slide	6.1 Stainless-steel round tube, operator side/customer side, fold-down	1553 x 235 mm
Tray slide	7.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 280 x 30 mm
Plate slide	8.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 153 x 30 mm
Side shelf	9.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	10.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Cond. water evap.	11.1 Electrical condensation-water evaporator	
Castor model	12.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	12.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard for line modules	13.1 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm	
	13.2 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through	
Module connection	13.3 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	

MIKADO – Heated servery counter 3 x GN 1/1

- Mobile module with 3 bain-marie wells, welded in without joints, for GN containers
- The bain-marie wells are individually heated indirectly wet or dry, 0.7 kW per well, and are equipped with a 1/2" drain
- Paneling: 18/10 stainless steel
- Top surface of 18/10 stainless steel, height of edge: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Operating modules on long side, installed ready to plug in incl. helix cord that can be drawn out to a length of approx. 2 m, Schuko plug, 230 V
- On/Off switch per well, On/Off switch for light and infrared radiator
- Separate, stepless temperature control for each well, temperature range: from +30°C to +95°C
- Sneeze guard on both sides of 6 mm thick, curved tempered safety glass (ESG), supported by two stainless-steel round-tube stands each
- Stainless-steel lighting and heating shelf with 3 low-voltage halogen lamps (3x20 W) and 2 ceramic radiators (2x150 W)
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO – WS-3 and WM-3

Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Capacity	Order No.
	MIKADO-WS-3	Heated servery counter with bain-marie technology, thin base	1217 x 675 x 1475 mm	3 x GN 1/1 max. depth: 200 mm	572 130
	MIKADO-WM-3	Heated servery counter with bain-marie technology, solid base	1217 x 675 x 1475 mm	3 x GN 1/1 max. depth: 200 mm	572 133

Equipment



Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1155 x 1250 mm
	2.2 yellow and white	
	2.3 blue and white	
	2.4 green and white	
Glass shelf	3.1 Glass shelf, tempered safety glass (ESG)	1085 x 270 x 8 mm
Railing	4.1 Railing for glass shelf, stainless-steel round tube	
Lighting and heating shelf	5.1 Stainless-steel with 3 low-voltage halogen lamps of 20 W each and 2 ceramic radiators with 150 W each	1115 x 80 x 40 mm
	5.2 Stainless-steel with 3 low-voltage halogen lamps of 20 W each and 2 ceramic radiators with 250 W each	
Tray slide	6.1 Stainless-steel round tube, operator side/customer side, fold-down	1228 x 235 mm
Tray slide	7.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1228 x 280 x 30 mm
Plate slide	8.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1228 x 153 x 30 mm
Side shelf	9.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	10.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Castor model	11.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	11.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard for line modules	12.1 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm	
	12.2 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through	
Module connection	12.3 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	

MIKADO – Heated servery counter 4 x GN 1/1

- Mobile module with 4 bain-marie wells, welded in without joints, for GN containers
- The bain-marie wells are individually heated indirectly wet or dry, 0.7 kW per well, and are equipped with a 1/2" drain
- Paneling: 18/10 stainless steel
- Top surface of 18/10 stainless steel, height of edge: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Operating modules on long side, installed ready to plug in incl. helix cord that can be drawn out to a length of approx. 2 m, Schuko plug, 230 V
- On/Off switch per well, On/Off switch for light and infrared radiator
- Separate, stepless temperature control for each well, temperature range: from +30°C to +95°C
- Temperature range: from +30°C to +95°C
- Sneeze guard on both sides of 6 mm thick, curved tempered safety glass (ESG), supported by two stainless-steel round-tube stands each
- Stainless-steel lighting and heating shelf with 4 low-voltage halogen lamps (4x20 W) and 3 ceramic radiators (3x150 W)
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO – WS-4 and WM-4

Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Capacity	Order No.
	MIKADO-WS-4	Heated servery counter with bain-marie technology, thin base	1542 x 675 x 1475 mm	4 x GN 1/1 max. depth: 200 mm	572 129
	MIKADO-WM-4	Heated servery counter with bain-marie technology, solid base	1542 x 675 x 1475 mm	4 x GN 1/1 max. depth: 200 mm	572 132

Equipment

Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1480 x 1250 mm
	2.2 yellow and white	
	2.3 Blue and white	
	2.4 green and white	
Glass shelf	3.1 Glass shelf, tempered safety glass (ESG)	1410 x 270 x 8 mm
Railing	4.1 Railing for glass shelf, stainless-steel round tube	
Lighting and heating shelf	5.1 Stainless-steel with 4 low-voltage halogen lamps of 20 W each and 3 ceramic radiators with 150 W each	1440 x 80 x 40 mm
	5.2 Stainless-steel with 4 low-voltage halogen lamps of 20 W each and 3 ceramic radiators with 250 W each	
Tray slide	6.1 Stainless-steel round tube, operator side/customer side, fold-down	1553 x 235 mm
Tray slide	7.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 280 x 30 mm
Plate slide	8.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 153 x 30 mm
Side shelf	9.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	10.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Castor model	11.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	11.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard for line modules	12.1 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm	
	12.2 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through	
Module connection	12.3 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	

MIKADO – Plain servery counter 3 x GN 1/1

- Mobile module with one-piece top surface of 18/10 stainless steel, edge height: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Paneling: 18/10 stainless steel
- Operating module on long side
- On/Off switch for light
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO – NS-3 and NM-3

Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Capacity	Order No.
	MIKADO-NS-3	Plain servery counter, thin base	1217 x 675 x 900 mm	same as 3 x GN 1/1	572 136
	MIKADO-NM-3	Plain servery counter, solid base	1217 x 675 x 900 mm	same as 3 x GN 1/1	572 139

Equipment



Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1155 x 1250 mm
	2.2 yellow and white	
	2.3 blue and white	
	2.4 green and white	
Sneeze guard for free-flow module, on both sides	3.1 Sneeze guard, on both sides, of 6 mm thick, curved tempered safety glass (ESG), with stainless-steel lighting shelf with 2 fluorescent tubes of 18 W each	
	3.2 Sneeze guard, on both sides, of 6 mm thick, curved tempered safety glass (ESG), with stainless-steel lighting shelf with 3 low-voltage halogen lamps of 20 W each	
Glass shelf	4.1 Glass shelf, tempered safety glass (ESG)	1085 x 270 x 8 mm
Railing	5.1 Railing for glass shelf, stainless-steel round tube	
Tray slide	6.1 Stainless-steel round tube, operator side/customer side, fold-down	1228 x 235 mm
Tray slide	7.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1228 x 280 x 30 mm
Plate slide	8.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1228 x 153 x 30 mm
Side shelf	9.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	10.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Castor model	11.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	11.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard for line modules	12.1 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm, with stainless-steel lighting shelf with 2 fluorescent tubes of 18 W each	
	12.2 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm, with stainless-steel lighting shelf with 3 low-voltage halogen lamps of 20 W each	
	12.3 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting shelf with 2 fluorescent lamps of 18 W each	
	12.4 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting shelf with 3 low-voltage halogen lamps of 20 W each	
Module connection	12.5 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	

MIKADO – Plain servery counter 4 x GN 1/1

- Mobile module with one-piece top surface of 18/10 stainless steel, edge height: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Paneling: 18/10 stainless steel
- Operating module on long side
- On/Off switch for light
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO – NS-4 and NM-4

Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Capacity	Order No.
NS-4 with accessories 	MIKADO-NS-4	Plain servery counter, thin base	1542 x 675 x 900 mm	same as 4 x GN 1/1	572 135
NM-4 with accessories 	MIKADO-NM-4	Plain servery counter, solid base	1542 x 675 x 900 mm	same as 4 x GN 1/1	572 138

Equipment


Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1480 x 1250 mm
	2.2 yellow and white	
	2.3 blue and white	
	2.4 green and white	
Sneeze guard for free-flow module, on both sides	3.1 Sneeze guard, on both sides, of 6 mm thick, curved tempered safety glass (ESG), with stainless-steel lighting shelf with 2 fluorescent tubes of 18 W each	
	3.2 Sneeze guard, on both sides, of 6 mm thick, curved tempered safety glass (ESG), with stainless-steel lighting shelf with 4 low-voltage halogen lamps of 20 W each	
Glass shelf	4.1 Glass shelf, tempered safety glass (ESG)	1410 x 270 x 8 mm
Railing	5.1 Railing for glass shelf, stainless-steel round tube	
Tray slide	6.1 Stainless-steel round tube, operator side/customer side, fold-down	1553 x 235 mm
Tray slide	7.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 280 x 30 mm
Plate slide	8.1 Resopal, operator side/customer side, fold-down, stone-grey decor	1553 x 153 x 30 mm
Side shelf	9.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	10.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Castor model	11.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	11.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard for line modules, one-sided	12.1 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm, with stainless-steel lighting shelf with 2 fluorescent lamps of 18 W each	
	12.2 Sneeze guard, one-sided, of 8 mm thick float glass, pass-through height 275 mm, with stainless-steel lighting shelf with 4 low-voltage halogen lamps of 20 W each	
	12.3 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting shelf with 2 fluorescent lamps of 18 W each	
	12.4 Sneeze guard, one-sided, of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting shelf with 4 low-voltage halogen lamps of 20 W each	
Module connection	12.5 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	

MIKADO – Servery counter AM-4

- Mobile line module with one-piece top surface of 18/10 stainless steel, edge height: 66 mm, radius at long sides: R = 15 mm, short sides turned down
- Roll-in niche (1290 mm x 500 mm) with CNS panel for rolling in
 - an SAW L-3 food serving trolley or
 - three Blancotherm food transport containers (in conjunction with 3x ROLA 13 or one middle shelf)
- In the roll-in niche, recessed at a height of 800 mm, 3 Schuko socket outlets are provided (230 V)
- Operating module on long side, installed ready to plug in with CEE plug, 400 V
- On/Off switch for light
- Paneling: 18/10 stainless steel
- Sneeze guard of 8 mm thick float glass, pass-through height 275 mm, supported by two stainless-steel round-tube stands each
- Stainless-steel lighting shelf with two fluorescent tubes (2x18 W)
- Castors with 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic, corrosion-resistant pursuant to DIN 18867-8



MIKADO – AM-4







Illustration	Model	Designation	Exterior dimensions L x W x H (mm)	Order No.
	MIKADO-AM-4	Servery counter	1542 x 675 x 1475 mm	572 803

Equipment

Designation	Design	Dimensions L x W x H (mm)
Paneling	1.1 Stainless steel	
	1.2 Stainless-steel backing, red, RAL 3020	
	1.3 Stainless-steel backing, yellow, RAL 1021	
	1.4 Stainless-steel backing, blue, RAL 5003	
	1.5 Stainless-steel backing, green, RAL 6024	
Fabric awning, removable	2.1 red and white	1480 x 1250 mm
	2.2 yellow and white	
	2.3 blue and white	
	2.4 green and white	
Lighting shelf	3.1 Stainless-steel with 2 fluorescent tubes of 18 W each	
	3.2 Stainless-steel with 4 low-voltage halogen lamps of 20 W each	
Lighting and heating shelf	4.1 Stainless-steel with 4 low-voltage halogen lamps of 20 W each and 3 ceramic radiators with 150 W each	
	4.2 Stainless-steel with 4 low-voltage halogen lamps of 20 W each and 3 ceramic radiators with 250 W each	
Tray slide	5.1 Stainless-steel round tube, on customer side, fold-down	1553 x 235 mm
Tray slide	6.1 Resopal, on customer side, fold-down, stone-grey decor	1553 x 280 x 30 mm
Plate slide	7.1 Resopal, on customer side, fold-down, stone-grey decor	1553 x 153 x 30 mm
Side shelf	8.1 Stainless-steel round tube, left/right-hand short end, fold-down	623 x 235 mm
Side shelf	9.1 Resopal, left/right-hand short end, fold-down, stone-grey decor	623 x 280 x 30 mm
Castor model	10.1 125 mm dia., 4 steering castors, 2 of which have brakes, synthetic pursuant to DIN 18867-8	
	10.2 125 mm dia., 4 steering castors, 2 of which have brakes, stainless-steel	
Sneeze guard pulled down, one-sided	11.1 Sneeze guard of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting shelf with 2 fluorescent tubes of 18 W each	
	11.2 Sneeze guard of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting shelf with 4 low-voltage halogen lamps of 20 W each	
	11.2 Sneeze guard of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting and heating shelf with 4 low-voltage halogen lamps of 20 W each and 3 ceramic radiators of 150 W each	
	11.2 Sneeze guard of 8 mm thick float glass, pulled down to top surface, without pass-through, with stainless-steel lighting and heating shelf with 4 low-voltage halogen lamps of 20 W each and 3 ceramic radiators of 250 W each	
Module connection	11.1 Module connection for line modules, 18/10 stainless steel (Order No. 572 773)	










accessories

Accessories and Equipment

Illustration	Model Designation	for MIKADO models	for modules	Dimensions L x W x H (mm)
	PANELING Stainless steel with a backing of coated sheet metal in: red (RAL 3020), blue (RAL 5003), green (RAL 6024) or yellow (RAL 1021)	all models	3 x GN 1/1	
			4 x GN 1/1	
	AWNING Fabric awning on stainless-steel supporting frame, removable, colours: red and white, blue and white, green and white or yellow and white	all models	3 x GN 1/1	1155 x 1220 mm
			4 x GN 1/1	1480 x 1250 mm
	GLASS SHELF without railing, of tempered safety glass (ESG)	all models	3 x GN 1/1	1085 x 270 x 8 mm
			4 x GN 1/1	1410 x 270 x 8 mm
	RAILING FOR GLASS SHELF of stainless-steel round tube	all models	3 x GN 1/1	
			4 x GN 1/1	
	HALOGEN LIGHTING SHELF of stainless-steel, with 3 or 4 low-voltage halogen lamps of 20 W each	MIKADO SK	3 x GN 1/1	1115 x 80 x 40 mm
		MIKADO SK MIKADO UK	4 x GN 1/1	1440 x 80 x 40 mm
	SNEEZE GUARD for free-flow modules with neon-tube lighting shelf Sneeze guard of tempered safety glass (ESG), stainless-steel lighting shelf, 2x18 W fluorescent tubes	MIKADO-N	3 x GN 1/1	
			4 x GN 1/1	
	SNEEZE GUARD for free-flow modules with halogen lighting shelf Sneeze guard of tempered safety glass (ESG), stainless-steel lighting shelf, with 3 or 4 low-voltage halogen lamps of 20 W each	MIKADO-N	3 x GN 1/1	
			4 x GN 1/1	
	LIGHTING/HEATING SHELF of stainless-steel, with 3 or 4 low-voltage halogen lamps with 20 W each and 2 or 3 ceramic radiators each of 250 W each	MIKADO-W	3 x GN 1/1	1115 x 80 x 40 mm
			4 x GN 1/1	1440 x 80 x 40 mm

accessories

Accessories and Equipment

Illustration	Model Designation	for MIKADO models	for modules	Dimensions L x W x H (mm)		
	SNEEZE GUARD for line modules, customer-side, with with neon-tube lighting shelf and pass-through (275 mm) Stainless-steel lighting shelf, fluorescent tubes, 2x18 W, cannot be combined with glass shelf and railing, float glass	MIKADO-SKM	3 x GN 1/1			
		MIKADO-UKM	4 x GN 1/1			
		MIKADO-WM				
		MIKADO-NM	3 x GN 1/1			
	SNEEZE GUARD for line modules, customer-side, with halogen lighting shelf and pass-through (275 mm) Stainless-steel lighting shelf, with 3 or 4 low-voltage halogen lamps of 20 W each, cannot be combined with glass shelf/railing, float glass	MIKADO-SKM	3 x GN 1/1			
		MIKADO-UKM				
		MIKADO-WM				
		MIKADO-NM	4 x GN 1/1			
	SNEEZE GUARD for line modules, pulled down to top surface on customer side with neon-tube lighting shelf Stainless-steel lighting shelf, fluorescent tubes, 2x18 W, cannot be combined with glass shelf and railing, float glass	MIKADO-SKM	3 x GN 1/1			
		MIKADO-UKM				
		MIKADO-WM				
		MIKADO-NM	4 x GN 1/1			
	SNEEZE GUARD for line modules, pulled down to top surface on customer side with halogen lighting shelf Stainless-steel lighting shelf, with 3 or 4 low-voltage halogen lamps of 20 W each, cannot be combined with glass shelf and railing, float glass	MIKADO-SKM	3 x GN 1/1			
		MIKADO-UKM				
		MIKADO-WM				
		MIKADO-NM	4 x GN 1/1			
	TRAY SLIDE fold-down, stainless-steel round tube, can be mounted on operator side and/or customer side	all models	3 x GN 1/1	1228 x 235 x 25 mm		
			4 x GN 1/1	1553 x 235 x 25 mm		
	TRAY SLIDE fold-down, Resopal-coated Multiplex board, stone-grey decor, with CNS-insert, can be mounted on operator side and/or customer side	all models	3 x GN 1/1	1228 x 235 x 25 mm		
			4 x GN 1/1	1553 x 235 x 25 mm		
	PLATE SLIDE fold-down, Resopal-coated Multiplex board, stone-grey decor, can be mounted on operator side and/or customer side	all models	3 x GN 1/1	1228 x 235 x 25 mm		
			4 x GN 1/1	1553 x 235 x 25 mm		
	SIDE SHELF fold-down, stainless-steel round tube, can be mounted on right and/or left-hand short side	all models	3 x GN 1/1	623 x 280 x 25 mm		
			4 x GN 1/1	623 x 280 x 25 mm		
	SIDE SHELF fold-down, Resopal-coated Multiplex board, stone-grey decor, can be mounted on right and/or left-hand short side	all models	3 x GN 1/1	623 x 280 x 25 mm		
			4 x GN 1/1	623 x 280 x 25 mm		
	STAINLESS-STEEL CASTORS Stainless-steel castor set, diameter 125 mm (4 castors, 2 of which have brakes)	all models				
not shown	MODULE CONNECTORS (Order No. 572 773)	all models				
not shown	ELECTR. CONDENSATION-WATER EVAPORATOR	MIKADO UK	4 x GN 1/1			

**LAS VEGAS – and there's virtually
no limit to what your imagination can do.**



From various modules you can design exactly the buffet you require.

The top and paneling design are freely selectable, and can therefore be matched to your personal room and furnishing concept.

Additional information available on request.

**MANHATTAN – Economy meets ergonomics.
Compact and flexible!**



Discover the unlimited possibilities of modern food servery. Whether hot or cold - MANHATTAN provides the ideal solution for any requirements.

The attractively priced complete line impresses with a flexible range of applications.

Additional information available on request.

